

SANI-21™

D3034 & F679 SEWER SPECIFICATION DATA

Nominal Pipe Size in. (mm)	A Outside Diameter Inches	B Bell Socket Diameter Inches	D Insert Mark Inches *	t Min. Wall Thickness SDR26/PS115 Inches	t Min. Wall Thickness SDR26/PS75 Inches	t Min. Wall Thickness SDR35/PS46 Inches
D-3034 PIPE DIMENSIONS						
4" (100)	4.215	5-1/4	4"	0.162		0.120
6" (150)	6.275	7-1/2	4-1/8"	0.241		0.180
8" (200)	8.400	9-7/8	4-7/8"	0.323		0.240
10" (250)	10.500	12-3/8	5-1/4"	0.404		0.300
12" (300)	12.500	14-5/8	5-1/2"	0.481		0.360
15" (375)	15.300	18	4-5/8"	0.588		0.437
F-679 PIPE DIMENSIONS						
18" (450)	18.701	21-3/4"	7-3/4"	0.671	0.584	0.499
21" (525)	22.047	25-1/2"	8-1/2"	0.791	0.689	0.588
24" (600)	24.803	28-3/4"	10"	0.889	0.775	0.661
27" (675)	27.953	32-1/2"	11-1/8"	1.002	0.874	0.745
30" ciod (750)	32.000	37-1/4"	13-5/8"	1.148	1.000	0.853
36" ciod (900)	38.300	43-1/4"	13-7/8"	1.373	1.197	1.021
42" ciod (1050)	44.500	53"	16-3/4"	1.596	1.391	1.187
48" ciod (1200)	50.800	60"	16-7/8"	1.822	1.588	1.355
54" ciod (1350)	57.560	67"	14"	2.064	1.799	1.535
60" ciod (1500)	61.610	72"	18"	2.210	1.926	1.643

SANI-21™

LOADING ASTM D3034 & F679 LOADING CHART

Nominal Pipe Size in. (mm)	Outside Diameter Inches	Bundle Quantity	*Feet Per Truckload	
			14'	20'
4" (100)	4.215	69	23,184	24,288
6" (150)	6.275	24/32	10,080	11,264
8" (200)	8.400	18/24	5544/6048	5808/6336
10" (250)	10.500	12/15	3402	3564
12" (300)	12.500	16	2688	2816
15" (375)	15.300	6	1512	1584
18" (450)	18.701	2/3/4/6	1050	1100
21" (525)	22.047	4	672	704
24" (600)	24.803	4	504/672	704
27" (675)	27.953	3	378	
30" (750)	32.000	3	378/252	
36" (900)	38.300	2	168	
42" (1050)	44.500	2	168	
48" (1200)	50.800	1	84	
54" (1350)	57.560	1	42	
60" (1500)	61.610	1	42	

Prices are subject to a firm policy of "Price in effect at time of shipment on regular purchases"

"Possession of this page does not constitute an offer of sale"

*Tolerance of +/- 1/4" allowed